



5W
REPLACEMENT

- 90+**
CRI
- 1W**
Watts
- E26**
- 120V**
Voltage
- WET LOCATION**

High quality of light and color rendering (90+ CRI, 50+ R9).





ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.176	70LM	1W	2450K	360°	>90	>0.7	-
SE-350.177	70LM	1W	2700K	360°	>90	>0.7	-
SE-350.178	70LM	1W	3000K	360°	>90	>0.7	-

MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.176	1.77in X 3.35in	0.53oz	-20°C - 40°C	12pcs	48pcs
SE-350.177	1.77in X 3.35in	0.53oz	-20°C - 40°C	12pcs	48pcs
SE-350.178	1.77in X 3.35in	0.53oz	-20°C - 40°C	12pcs	48pcs






RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES						
R1=95	R2=98	R3=99	R4=95	R5=95	R6=93	R7=90
R8=83	R9=65	R10=95	R11=96	R5=87	R13=96	R14=99



TM30 GRAPHIC

TM-30 deals with the color rendition of object.

R_f- a fidelity index that is similar to the commonly used CRI

R_g- a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

