



**40W**  
REPLACEMENT

**90+**  
CRI

**3.8W**  
Watts

**E26**

**120V**  
Voltage

**DAMP LOCATION**

**Dimmable**

High quality of light and color rendering (90+ CRI, 50+ R9),  
Smooth dimming. Dimming lower than 20%.





## ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.120	350LM	3.8W	2200K	360°	>90	>0.7	-

## MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.120	2.36in X 4.06in	1.23oz	-20°C - 40°C	12pcs	48pcs






## RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES						
R1=92	R2=98	R3=97	R4=91	R5=93	R6=98	R7=88
R8=77	R9=53	R10=95	R11=93	R12=87	R13=94	R14=99



## TM30 GRAPHIC

TM-30 deals with the color rendition of object.

R<sub>f</sub> - a fidelity index that is similar to the commonly used CRI

R<sub>g</sub> - a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

