

90+ LIGHTING A19 SILVER TIP 6.2W



40W
REPLACEMENT

90+
CRI

6.2W
Watts

E26

120V
Voltage

DAMP LOCATION

Dimmable

High quality of light and color rendering (90+ CRI, 50+ R9),
Smooth dimming. Dimming lower than 20%.




ELECTRICAL SPECIFICATIONS


| MODEL NO. | LUMEN | POWER | CCT | BEAM | CRI | PF | CBCP |
|------------|-------|-------|-------|------|-----|------|------|
| SE-350.116 | 420LM | 6.2W | 2500K | 360° | >90 | >0.7 | - |

MECHANICAL SPECIFICATIONS

| MODEL NO. | MEASURES | WEIGHT | OPERATIONAL TEMPERATURE | INNER BOX QTY | MASTER CARTON QTY |
|------------|-----------------|--------|-------------------------|---------------|-------------------|
| SE-350.116 | 2.36in X 4.06in | 1.23oz | -20°C - 40°C | 12pcs | 48pcs |



90+ LIGHTING A19 SILVER TIP 6.2W




RA - CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES

| | | | | | | |
|-------|-------|--------|--------|--------|--------|--------|
| R1=95 | R2=99 | R3=94 | R4=92 | R5=95 | R6=95 | R7=88 |
| R8=78 | R9=58 | R10=99 | R11=95 | R12=86 | R13=97 | R14=98 |



TM30 GRAPHIC

TM-30 deals with the color rendition of object.

R_f - a fidelity index that is similar to the commonly used CRI

R_g - a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

