



60W  
REPLACEMENT

90+  
CRI

7W  
Watts

E26

120V  
Voltage

DAMP LOCATION

Dimmable

High quality of light and color rendering (90+ CRI, 50+ R9),  
 with low flicker, flicker <30%,  
 Smooth dimming. Dimming lower than 10%.






## ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.198	810LM	7W	2700K	360°	>90	>0.9	-

## MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.198	2.28in X 5.12in	1.23oz	-20°C - 40°C	12pcs	48pcs






## RA - CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES						
R1=93	R2=97	R3=100	R4=94	R5=93	R6=98	R7=90
R8=80	R9=56	R10=92	R11=96	R12=85	R13=94	R14=99



## TM30 GRAPHIC

TM-30 deals with the color rendition of object.

$R_f$  - a fidelity index that is similar to the commonly used CRI

$R_g$  - a gamut index that provides information about saturation

Color vector graphic - a graphical representation of hue and saturation relative to a reference source.

