



**60W**  
REPLACEMENT

<b>90+</b> CRI	<b>5,5W</b> Watts
<b>E12</b>	<b>120V</b> Voltage
<b>DAMP LOCATION</b>	<b>Dimmable</b>

High quality of light and color rendering (90+ CRI, 50+ R9),  
with low flicker, flicker <30%,  
Smooth dimming. Dimming lower than 10%.





## ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.205	500LM	5.5W	2700K	360°	>90	>0.9	-

## MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.205	1.38in X 3.82in	0.71oz	-20°C - 40°C	12pcs	48pcs






## RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES						
R1=94	R2=97	R3=99	R4=94	R5=94	R6=98	R7=91
R8=81	R9=60	R10=94	R11=96	R12=85	R13=95	R14=99



## TM30 GRAPHIC

TM-30 deals with the color rendition of object.

Rf- a fidelity index that is similar to the commonly used CRI

Rg- a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.