



40W
REPLACEMENT

90+ CRI	120V Voltage
 E12	3.3W Watts
 DAMP LOCATION	 Dimmable

High quality of light and color rendering (90+ CRI, 50+ R9),
Smooth dimming. Dimming lower than 20%.





ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.119	300LM	3.3W	2200K	360°	>90	>0.9	-

MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.119	1.38in X 4.06in	0.71oz	-20°C - 40°C	12pcs	48pcs





RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES						
R1=93	R2=98	R3=96	R4=91	R5=93	R6=97	R7=88
R8=77	R9=54	R10=96	R11=93	R12=87	R13=94	R14=99



TM30 GRAPHIC

TM-30 deals with the color rendition of object.

R_f- a fidelity index that is similar to the commonly used CRI

R_g- a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

